

UL Online Certifications Directory

KDER.E90057 Grounding and Bonding Equipment

[Page Bottom](#)

Grounding and Bonding Equipment

[See General Information for Grounding and Bonding Equipment](#)

L H DOTTIE CO
6131 S GARFIELD AVE
COMMERCE, CA 90040 USA

E90057

Ground clamp for making connection between No. 4, 6 or 8 Awg wire and 1/2, 3/4, or 1-in. ground pipe, rigid conduit or grounding electrode.

Ground clamp for making connection between No. 4, 6 or 8 Awg wire and 1 1/4, 1-1/2 or 2-in. ground pipe, rigid conduit or grounding electrode.

Protective type ground clamp for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1/2 in. rigid conduit.

Protective type ground clamp for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1/2, 3/4 and 1-in. pipe.

Protective type ground clamp for making connection between armor of No. 4, 6 or 8 Awg bare armored conductor and 1-1/4, 1-1/2, and 2-in. pipe.

Ground rod clamp for direct burial. Sizes 1/2" through 3/4". Cat. Nos. GR-12, -34, -58.

Bronze ground clamp for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2" through 6". Cat. Nos. 25, 27, 250, PL25, 1001, 1002, DB-25, -27 for direct burial.

Bronze ground pipe clamp for bare or armored wire, for making connection between bare or armored wire and galvanized water pipe. Sizes 1/2" through 4". Cat. Nos. 26, 28, 26SWV.

Ground clamp for rigid conduit, brass body, Cat. Nos. 29, 30, 31, 270, 271, 272.

Grounding bushings, Cat. Nos. GB, GBL-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Grounding clip for connecting bare copper or aluminum grounding conductor of nonmetallic sheathed cable to an outlet box and for connecting humper from a receptacle to an outlet box, Cat. No. GC.

Bronze ground pipe clamp for rigid conduit or intermediate metallic conduit, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Sizes 1/2" through 4". Cat. Nos. 29L, 30L, 31L, 270L, 271L, 272L, 280L, 281L, 290L, 291L, 292L, 29L-BB, 30L-BB, 31L-BB.

Conduit hubs, sizes 1/2" through 1". Cat. Nos. HUB-50L, -75L, -100L.

Ground bushing, zinc, with 150 C rated nylon insulator and aluminum lug. Sizes 1/2" through 4". Cat. Nos. GB-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Ground bushing, zinc with 150 C rated nylon insulator and C-Clamp lay-in lug. Sizes 1/2" through 4". Cat. Nos. GBL-50, -75, -100, -125, -150, -200, -250, -300, -350, -400.

Bronze ground pipe clamp for bare wire, for making connection between copper grounding conductor, galvanized water pipe, copper water tubing or copper ground rod. Size 1/2" through 6". Also for steel rebar sizes : 5 and 6. For direct burial in earth and concrete Cat. No. DB-25.

Grounding electrodes, Cat. Nos. GR5808, -3410, -1208, -5810, -3408.

Ground clamps for making connections between 1/2 to 1-1/4 in. pipe and 10-2 AWG copper, Cat. Nos. 20, -21, followed by M or B.

Last Updated on 2002-08-03

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2006 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2006 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

