



Dottie Pipe Wrap

PVC Pipe Wrap Tape UPC Approved



**Uniform
Plumbing
Code**



- Thickness:** 10 Mil & 20 Mil
- Tensile strength** (lbs/in width): 20
- Adhesion** (oz/in width) to primed steel: 110
- Adhesion** (oz/in width) to un-primed steel: 75
- Elongation:** 200%
- Temperature range:** -30 degrees F to 140 degrees F
- Low Lead Product**

UPC Approved; Provides excellent insulation; Durable polyethylene backing; Ideal for iron and steel; Corrosion resistant. It has a super tack adhesion for extra holding power. It is used a lot by underground pipe contractors and plumbers to protect iron and steel pipe from corrosion due to high acidic or "hot soils".

It is also used to protect pvc pipe from corrosion due to ultraviolet rays in above ground installations.

This tape is also used in the oilfield industry to wrap above and underground pipes to prevent corrosion due to the high methane levels in the soil around oil fields.

Pipe Wrap - PVC PC 5420

Pipe Wrap is a polyvinyl chloride film coated with a rubber resin adhesive which protects pipe, joints, conduit and couplings for overhead or direct burial applications. It is corrosion and puncture resistant.

- 1", 2" & 4" Widths
- UPC Approved
- 10 Mil and 20 Mil
- Abrasion Resistant
- Provides Electrical Protection

CAT NO	UPC	DIMENSIONS	MIL	STD	MSTR	WT/STD	UNIT
110	28110	1" x 100'	10 Mil	48	48	29.28#	Ea
210	28140	2" x 100'	10 Mil	24	24	28.80#	Ea
410	28142	4" x 100'	10 Mil	12	12	27.60#	Ea
220	28145	2" x 100'	20 Mil	24	24	53.52#	Ea