



ZODZ.E478898 Positioning Devices

Page Bottom

Positioning Devices

[See General Information for Positioning Devices](#)

L H DOTTIE CO

6131 GARFIELD AVE
COMMERCE, CA 90040-3610 USA

E478898

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg	Bundle Diam, mm (in.)		Loop Tensile Strength, N (lbf)	Operating Temp, °C (°F)		Min Installation Temp, °C (°F)	Resistant to UV Light	Plenum Rating	ANSI/UL 94 Mtl Flame Rating
		Min	Max		Min	Max				
DT4B	21	1.57 (0.062)	22.2 (0.874)	80 (18)	-40	85	0	Yes	AH-2	V-2
DT4BBULK	21	1.57 (0.062)	22.2 (0.874)	80 (18)	-40	85	0	Yes	AH-2	V-2
DT5B	21	1.57 (0.062)	36.5 (1.437)	178 (40)	-40	85	0	Yes	AH-2	V-2
DT5BBULK	21	1.57 (0.062)	36.5 (1.437)	178 (40)	-40	85	0	Yes	AH-2	V-2
DT6B	21	1.57 (0.062)	47.6 (1.875)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT6BBULK	21	1.57 (0.062)	47.6 (1.875)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT11B	21	1.57 (0.062)	77.7 (3.062)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT11BBULK	21	1.57 (0.062)	77.7 (3.062)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT14B	21	1.57 (0.062)	101.6 (4.0)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT14BBULK	21	1.57 (0.062)	101.6 (4.0)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT14HB	21	4.75 (0.187)	103.1 (4.06)	534 (120)	-40	85	0	Yes	AH-2	V-2
DT21HB	21	38.1 (1.5)	182.3 (7.18)	778 (175)	-40	85	0	Yes	AH-2	V-2
DT36HB	21	38.1 (1.5)	279.4 (11.0)	222 (50)	-40	85	0	Yes	AH-2	V-2
DT4	21	1.57 (0.062)	22.2 (0.875)	80 (18)	-40	85	0	N/A	AH-2	V-2
DT4BULK	21	1.57 (0.062)	22.2 (0.875)	80 (18)	-40	85	0	N/A	AH-2	V-2
DT5	21	1.57 (0.062)	36.4 (1.437)	178 (40)	-40	85	0	N/A	AH-2	V-2

DT5BULK	21	1.57 (0.062)	36.4 (1.437)	178 (40)	-40	85	0	N/A	AH-2	V-2
DTP6	21	1.57 (0.062)	47.6 (1.875)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT6	21	1.57 (0.062)	47.6 (1.875)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT6BULK	21	1.57 (0.062)	47.6 (1.875)	222 (50)	-40	85	0	N/A	AH-2	V-2
DTP11	21	1.57 (0.062)	77.7 (3.062)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT11	21	1.57 (0.062)	77.7 (3.062)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT11BULK	21	1.57 (0.062)	77.7 (3.062)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT14H	21	4.75 (0.187)	103.1 (4.06)	534 (120)	-40	85	0	N/A	AH-2	V-2
DT21H	21	38.1 (1.5)	182.3 (7.18)	778 (175)	-40	85	0	N/A	AH-2	V-2
DT36H	21	152.4 (6.0)	38.1 (1.5)	778 (175)	-40	85	0	N/A	AH-2	V-2
DT48G	21	152.4 (6.0)	38.1 (1.5)	778 (175)	-40	85	0	N/A	AH-2	V-2
DTP14	21	1.58 (0.062)	101.60 (4.0)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT14	21	1.58 (0.062)	101.60 (4.0)	222 (50)	-40	85	0	N/A	AH-2	V-2
DT14BULK	21	1.58 (0.062)	101.60 (4.0)	222 (50)	-40	85	0	N/A	AH-2	V-2

Last Updated on 2015-09-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".